

Hybrid Ockhamist Temporal Logic

Patrick Blackburn
INRIA, Lorraine
Campus Scientifique, BP 239
Nancy, France
patrick@aplog.org

Valentin Goranko
Department of Mathematics
Rand Afrikaans University
Johannesburg, South Africa
vfg@na.rau.ac.za

Abstract

We introduce hybrid Ockhamist temporal logic, which combines the mechanisms of hybrid logic with Ockhamist semantics by employing nominals, satisfaction operators, binders, and quantifiers over branches. We provide a complete (with respect to bundled trees semantics) axiomatic system for the basic hybrid Ockhamist temporal logic (HOT) and for some of its extensions, including the full hybrid Ockhamist temporal logic. The full system is expressively equivalent to the first-order logic over trees extended with branch quantifiers which was proved decidable by Gurevich and Shelah.

1. Introduction

Hybrid Ockhamist temporal logics combine two ideas well known in temporal logic: *Ockhamist semantics* and *hybrid logic* (not to be confused with the ‘hybrid systems’ which combine discrete transition systems with continuous dynamical systems).

Ockhamist semantics for temporal logic (see [16], [18], [19]) is based on the idea that while the future is non-deterministic (that is, events can take different courses) the actual future, which is bound to happen, is deterministic. Formally, this means that, although the flow of time is a forward branching tree, when a formula is to be evaluated a possible ‘actual future’ is fixed (that is, a branch of the tree is selected) and the evaluation is done with respect to that branch. Thus, a temporal model for Ockhamist semantics is a tree-like structure, the branches of which are the primitive entities with respect to which the formulae are evaluated, and the basic notion of truth of a formula is relative to a branch of the future, rather than an instant of time. Ockhamist semantics is the underlying semantics of the branching time temporal logics of computation CTL and CTL* (see [12], [17]).

Hybrid temporal (and modal) logic dates back to Prior

([16]) and Bull ([10]) and has been actively developed recently (see [6], Chapter 6 of [8], and www.hylo.net, the hybrid logic homepage, for more information). Modern hybrid logic extends modal or temporal logic with various mechanisms for naming and quantifying over possible worlds or times, mechanisms such as *nominals*, *satisfaction operators*, *binders*, and *quantifiers*. Such mechanisms increase the expressive power of the underlying temporal (or modal) logic in a natural way, and in many interesting cases their introduction does not raise the computational complexity (see [2]). Moreover, hybrid logic has a number of relatives. For example, it is closely related to *description logic* (see [1]). In addition, a formalism called *half-order modal logic*, using *freeze quantifiers* to bind variables to the content of the current instant of evaluation, was independently introduced, developed, and applied to real-time logics by Alur and Henzinger (see [3], [15], [4]). Freeze quantification is related to the \downarrow binder used in some strong hybrid logics (we introduce such a system at the end of the present paper).

In a precursor of the present work, [9], Ockhamist temporal logic was extended with special variables (*fan variables*) ranging over sets of branches sharing the same beginning, and a *difference operator* on branches. The idea of hybrid temporal logic with nominals and binders over paths was briefly discussed in [7]. The purpose of the present paper is to introduce, axiomatize, and study the basic hybrid Ockhamist temporal logic. We first ‘hybridize’ ordinary Ockhamist temporal logic by adding the basic referential tools of hybrid logic: nominals and satisfaction operators. At the end of the paper we look at stronger systems: logics in which the underlying temporal formalism contains Until and Since operators, logics with the \downarrow binder, and logics with path quantifiers.

2. The basic hybrid Ockhamist propositional temporal logic HOT

In this section we introduce the hybrid language we shall work with for most of the paper, and discuss two (equiva-

lent) semantics for it: the bundled tree semantics, and Ockhamist frame semantics.

2.1. Syntax

The language of HOT contains propositional logical connectives \perp, \rightarrow ; temporal modalities F, P ; a modality \diamond for a **possible alternative future**; a denumerable set $PV = \{p_0, p_1 \dots\}$ of propositional variables; a denumerable set $BN = \{b_0, b_1 \dots\}$ of **branch nominals**; and a **branch retriever (pointer) @**.

Formulas of HOT are defined recursively as follows:

$$\varphi = \perp \mid p \mid \mathbf{b} \mid \varphi \rightarrow \varphi \mid P\varphi \mid F\varphi \mid \diamond\varphi \mid @_{\mathbf{b}}\varphi.$$

We make use of the following *defined operators*:

- $\langle \leq \rangle \varphi = \varphi \vee F\varphi$, (sometime now or in this future);
- $\langle \geq \rangle \varphi = \varphi \vee P\varphi$, (sometime now or in the past);
- $E\varphi := \langle \geq \rangle \diamond \langle \leq \rangle \varphi$, (in tree-like structures: sometime);
- $\langle \pi \rangle \varphi = P\varphi \vee \varphi \vee F\varphi$, (sometime along this time path).

Furthermore, by G, H, A, \square , and $[*]$ we denote the respective duals of F, P, E, \diamond and $\langle * \rangle$.

2.2. Bundled trees and Ockhamist frames

Not all branches in a tree are needed in order to give reasonable Ockhamist semantics, but *sufficiently many* of them must be considered. Three conditions seem necessary for a family of branches to be regarded as large enough for the purpose (see [12]):

- (i) *Every time instant must belong to a branch from the family;*
- (ii) *Every sub-branch of a branch from the family must belong to the family.*
- (iii) *Every extension of a branch from the family must belong to the family.*

Such a family of branches will be called a **bundle**, and the Ockhamist semantics will be defined on such bundles, considering the branches in them as *primitive entities*. A **complete bundle** is a bundle containing all branches in the tree. Complete bundles are obtained when a bundle is closed under *limits of converging sequences of branches*.

We now proceed with a formal exposition of Ockhamist semantics.

Definition 2.1 A **tree** T is a strict partial ordering $\langle M, < \rangle$, such that every **node** $x \in M$ has a linear set of $<$ -predecessors.. The least element of a tree, if it exists, is called the **root**, and then the tree is called **rooted**.

Definition 2.2 Let $T = (M, <)$ be a tree. A **path** in T is a maximal linearly ordered set of nodes. A **branch** in T is any set of nodes of the type $\{y \mid y \in \pi \text{ and } x \leq y\}$ for some path π and $x \in \pi$. The least node x of a branch b is the **initial node** of b , denoted by $I(b)$. Thus, every branch is an upwards closed part of a path, with an initial node. When T is rooted, every path is a (maximal) branch in T .

Definition 2.3 Let b, c be branches in a tree and $c \supseteq b$. Then b is called a **sub-branch** of c , and c is an **extension** of b . This we shall denote by $c \trianglelefteq b$. Note that \trianglelefteq is a partial ordering on branches.

In particular, if $x \in b$ then b_x is the sub-branch of b with $I(b_x) = x$.

If $c \supsetneq b$ then b is a **proper sub-branch** of c , and c is a **proper extension** of b , denoted by $c \triangleleft b$.

Two branches are called **siblings** if they have the same initial node. Siblinghood is an equivalence relation on the set of branches in a tree, denoted by \sim .

We denote the set of all branches in a tree T by $\mathbf{B}(T)$.

Definition 2.4 (See [19]) A **bundled tree** is a pair (T, \mathcal{B}) where T is a tree and \mathcal{B} is a non-empty set of branches (called a **bundle**) in T , closed under sub-branches and extensions and such that every node of T belongs to some branch from \mathcal{B} .

A **path** in (T, \mathcal{B}) is a path in T all of whose branches are in \mathcal{B} . Note that if *some* branch from the path is in the bundle, then all of them are there. Thus a bundle consists of all branches along paths covering the nodes of the tree. An equivalent structure to a bundled tree is an **Ockhamist frame**: a triple $\langle W, \triangleleft, \sim \rangle$ where W is a set, \triangleleft is a union of irreflexive linear orderings in W , \sim is an equivalence relation on W satisfying certain first-order definable conditions (see [19]). The elements of an Ockhamist frame can be thought as branches in a bundle on a tree obtained by identifying the \sim -equivalent points, defining $<$ as the quotient-relation of \triangleleft . Conversely, with every bundled tree one can associate the Ockhamist frame consisting of the branches in the bundle, with the relations defined as above. Thus, as Zanardo has shown in [19], bundled trees and Ockhamist frames are interdefinable, hence equivalent as semantic structures.

2.3. Ockhamist truth and validity in bundled trees

We interpret our hybrid language in the following type of model:

Definition 2.5 A *valuation* on a bundled tree $\mathcal{T} = (\langle M, < \rangle, \mathcal{B})$ is any mapping $V : (BN \cup PV) \rightarrow 2^{\mathcal{B}}$ such that for every $\mathbf{b} \in BN$, $V(\mathbf{b})$ is a singleton. Hereafter we will be writing $V(\mathbf{b}) = b$ instead of $V(\mathbf{b}) = \{b\}$.

A *model* is a pair (\mathcal{T}, V) where \mathcal{T} is a bundled tree and V is a valuation in \mathcal{T} .

Note that this definition is standard, save for the demand that branch nominals be interpreted by *singleton* sets of branches. That is, in any model, branch nominals are true at a *unique* branch. In effect, they ‘name’ the unique branch they are true at — thus branch nominals are a simple modal mechanism for referring to branches.

We can now define **(Ockhamist) truth** of a formula in a model *relative to a branch* b in that model:

- $\mathcal{M}, b \models \mathbf{b}$ iff $V(\mathbf{b}) = b$, for any $\mathbf{b} \in BN$;
- $\mathcal{M}, b \models p$ iff $b \in V(p)$, for any $p \in PV$;
- $\mathcal{M}, b \not\models \perp$;
- $\mathcal{M}, b \models \varphi \rightarrow \psi$ iff $\mathcal{M}, b \models \varphi$ implies $\mathcal{M}, b \models \psi$;
- $\mathcal{M}, b \models F\varphi$ iff for some $c \triangleright b$, $\mathcal{M}, c \models \varphi$;
- $\mathcal{M}, b \models P\varphi$ iff for some $c \triangleleft b$, $\mathcal{M}, c \models \varphi$;
- $\mathcal{M}, b \models \diamond\varphi$ iff for some $c \sim b$, $\mathcal{M}, c \models \varphi$;
- $\mathcal{M}, b \models @_{\mathbf{b}}\varphi$ iff $\mathcal{M}, V(\mathbf{b}) \models \varphi$;

As promised, the first clause of this definition guarantees that nominals are true at (and hence name) a unique branch in the model. But note also the last clause. The meaning of the construct $@_{\mathbf{b}}\varphi$ is: *go to the branch named \mathbf{b} and see if φ is true there*. That is, $@$ ‘retrieves’ the value of \mathbf{b} and evaluates φ at that branch. In the hybrid logic literature, operators like $@_{\mathbf{b}}$ are usually called **satisfaction operators**.

A formula is: **(Ockhamist)-valid in a model** if it is true at every branch of that model; **(Ockhamist)-valid in a bundle tree** if it is Ockhamist-valid in every model on that bundle tree; **valid** if it is Ockhamist-valid in every bundle tree.

2.4. Ockhamist semantics and Kripke semantics

Ockhamist semantics can be related to Kripke semantics in several ways. First of all, one can formally consider bundle trees or Ockhamist frames just as Kripke frames for a 3-modal logic with modalities F, P, \diamond . Save for the fact that the possible worlds in these frames in fact represent particularly structured sets of points (viz. branches), the Ockhamist semantics is just a traditional Kripke semantics for Ockhamist frames. For detailed treatment of that approach see [19].

Apart from this formal analogy, a temporal Kripke frame $\langle M, < \rangle$ can be viewed as representing a time flow by regarding $<$ either as a *precedence relation* between time instants (in which case it must be at least a partial ordering) or as a *successor relation* between consecutive instants in a discrete flow of time (in which case no assumptions on it need to be made). The former interpretation is the traditional one in the classical framework of temporal logic, while the latter one is the interpretation in linear or branching time temporal logics of computations prominent in computer science. The latter interpretation can be transformed into the former by taking the *transitive closure* of the successor relation as the one representing the precedence relation between instants. We can therefore concentrate on the classical interpretation.

Given a temporal frame $T = \langle M, < \rangle$ with $<$ being a (strict) partial ordering, a **possible future of an instant** $t \in T$ is a *maximal linearly ordered set* in $\{s \mid t \leq s\}$, also called a **branch in T stemming from t** . Now, let $\mathbf{B}(T)$ be the set of all branches in T . We can introduce a partial ordering on $\mathbf{B}(T)$ by defining $\mathbf{b} \preceq \mathbf{c}$ if $\mathbf{b} \supseteq \mathbf{c}$, (the idea being that the beginning of \mathbf{b} precedes the one of \mathbf{c}). It is easy to see that the resulting structure is a bundle on the *unwinding* of T into a tree. Thus, Ockhamist semantics can be introduced on any partial ordering, or even on any Kripke frame $\langle M, R \rangle$ by regarding the relation as a successor relation and unwinding.

3. Axiomatic system for HOT

3.1. Axioms for the modalities:

(**K**) The **K** axiom for each of F, P, \diamond ;

(**FP**) The temporal axioms for F, P :

$$\mathbf{b} \rightarrow HF\mathbf{b} \wedge GP\mathbf{b}.$$

(**S5** \diamond) The **S5** axioms for \diamond .

(**S5A**) The **S5** axioms for the universal modality $Ap = [\geq] \square [\leq] p$

(**@**) The defining axiom for $@$: $@_{\mathbf{b}}\varphi \longleftrightarrow A(\mathbf{b} \rightarrow \varphi)$.

3.2. Axioms for the nominals:

(**NOM1**) $E\mathbf{b}$,

(**NOM2**) $E(\mathbf{b} \wedge \varphi) \rightarrow A(\mathbf{b} \rightarrow \varphi)$,

(**FUN@**) Alternatively to the two above: $\neg @_{\mathbf{b}} \neg \varphi \longleftrightarrow @_{\mathbf{b}} \varphi$;

3.3. Axioms for the structure:

- (SI) $c \rightarrow \Box G \Box \neg c$ ('strong' irreflexivity);
 (TR) $FFc \rightarrow Fc$ (transitivity);
 (LP) $(FPc \vee PFc) \rightarrow \langle \pi \rangle c$ (linearity of paths);
 (DP) $c \rightarrow \Box H \Diamond Fc$; (determinacy of the past);
 (DB) $c \rightarrow \Box (G \Diamond Pc \rightarrow c)$ (distinguishability of branches);

For rooted trees we add:

- (RT) $\langle \leq \rangle H \perp$; (root);

3.4. Rules of inference:

- *Modus Ponens*;
- *Necessitation (NEC)* for each of G, H, \Box ;
- *Uniform substitution (SUB)* of formulas for variables and nominals for nominals.
- *NAME*:

$$\frac{\mathbf{b} \rightarrow \theta \text{ for some nominal } \mathbf{b} \text{ not occurring in } \theta}{\theta}$$

Remark 3.1 The following rule schema (PASTE) is derivable.

$$\frac{\@_{\mathbf{b}\blacktriangle}(c \wedge \varphi) \rightarrow \theta \text{ for some nominal } \mathbf{c} \text{ not occurring in } \theta \text{ and } \varphi}{\@_{\mathbf{b}\blacktriangle}\varphi \rightarrow \theta}$$

where \blacktriangle is F, P , or \Diamond .

Theorem 3.2 The logic HOT is sound and complete for the bundle trees semantics.

Proof (sketch):

1. Soundness is straightforward. The completeness proof begins with a canonical model construction using special maximal HOT-theories. These are maximal consistent sets closed under NAME and PASTE. Standard lemmas, such as the Lindenbaum lemma, are provable for HOT-theories.
2. Suppose the canonical model is now constructed. Given a consistent formula φ , take a maximal HOT-theory Γ containing φ .
3. Define $\mathbf{b} \equiv_{\Gamma} \mathbf{c}$ if $E(\mathbf{b} \wedge \mathbf{c}) \in \Gamma$.
4. CLAIM 1: \equiv_{Γ} is an equivalence relation on BN .

5. For each equivalence class of \equiv_{Γ} we select a representative (e.g. the one with the least index) and let \mathbf{B}_{Γ} be the set of these representatives. \mathbf{B}_{Γ} presents the generated by Γ submodel of the canonical model.
6. Define for any $\mathbf{c}, \mathbf{d} \in \mathbf{B}_{\Gamma}$:

$$\mathbf{c} \sim \mathbf{d} \text{ iff } E(\mathbf{c} \wedge \Diamond \mathbf{d}) \in \Gamma; \quad \mathbf{c} < \mathbf{d} \text{ iff } E(\mathbf{c} \wedge F \mathbf{d}) \in \Gamma.$$

7. CLAIM 2: \sim is an equivalence relation.
8. CLAIM 3: $<$ is a strict partial ordering.
9. Now: define $\mathbf{W}_{\Gamma} = \{\tilde{\mathbf{c}} \mid \mathbf{c} \in \mathbf{B}_{\Gamma}\}$. On \mathbf{W}_{Γ} define

$$\tilde{\mathbf{c}} \prec \tilde{\mathbf{d}} \text{ iff } \@_{\mathbf{c}} \Diamond F \mathbf{d}.$$

Intuition: the elements of \mathbf{W}_{Γ} represents the nodes of a tree, and \prec is the precedence relation between them.

10. CLAIM 4: The following are equivalent:

- $\tilde{\mathbf{c}} \prec \tilde{\mathbf{d}}$
- $@_{\mathbf{d}} P \Diamond \mathbf{c}$
- $\mathbf{c}' < \mathbf{d}'$ for some $\mathbf{c}' \sim \mathbf{c}, \mathbf{d}' \sim \mathbf{d}$
- for every $\mathbf{d}' \sim \mathbf{d}$ there is a $\mathbf{c}' \sim \mathbf{c}$ such that $\mathbf{c}' < \mathbf{d}'$.

11. CLAIM 5: \prec is a strict partial ordering on \mathbf{W}_{Γ} and $\langle \mathbf{W}_{\Gamma}, \prec \rangle$ is a (rooted) tree.

12. Furthermore, with every $\mathbf{c} \in \mathbf{B}_{\Gamma}$ we associate a set $B_{\mathbf{c}}$ in \mathbf{W}_{Γ} as follows:

$$\begin{aligned} B_{\mathbf{c}} &= \left\{ \tilde{\mathbf{d}} \mid \@_{\mathbf{c}} (\Diamond \mathbf{d} \vee F \Diamond \mathbf{d}) \in \Gamma \right\} = \\ &= \left\{ \tilde{\mathbf{d}} \in \mathbf{W}_{\Gamma} \mid \mathbf{c} \leq \mathbf{d}' \text{ for some } \mathbf{d}' \sim \mathbf{d} \right\} \\ &= \left\{ \tilde{\mathbf{d}} \in \mathbf{W}_{\Gamma} \mid \mathbf{c} \leq \mathbf{d} \right\}. \end{aligned}$$

13. CLAIM 6: $B_{\mathbf{c}}$ is a branch in \mathbf{W}_{Γ} .

14. Now we define $B_{\mathbf{c}} \smile B_{\mathbf{d}}$ iff $\mathbf{c} \sim \mathbf{d}$ and $B_{\mathbf{c}} \triangleleft B_{\mathbf{d}}$ iff $\mathbf{c} < \mathbf{d}$. Thus: $\langle \mathbf{B}_{\Gamma}, <, \sim \rangle \cong \langle \{B_{\mathbf{c}}\}_{\mathbf{c} \in \mathbf{B}_{\Gamma}}, \triangleleft, \smile \rangle$.

15. CLAIM 7: $\mathfrak{T}_{\Gamma} = \langle \mathbf{W}_{\Gamma}, \{B_{\mathbf{c}}\}_{\mathbf{c} \in \mathbf{B}_{\Gamma}} \rangle$ is a bundle tree.

16. Now, the canonical valuation V_{Γ} on \mathfrak{T} : $V_{\Gamma}(\mathbf{c}) = B_{\mathbf{c}}$; $V_{\Gamma}(p) = \{B_{\mathbf{b}} \mid \@_{\mathbf{b}} p \in \Gamma\}$.

17. CLAIM 8: (Truth lemma) for every formula φ and $\mathbf{c} \in BN$:

$$\mathfrak{T}_{\Gamma}, V_{\Gamma}, B_{\mathbf{c}} \models \varphi \text{ iff } \@_{\mathbf{c}} \varphi \in \Gamma.$$

18. Now the completeness follows immediately. QED.

A general remark. As we stated in Step 1 of the proof sketch, the basic idea of the completeness proof is to use a modal canonical model construction. Nonetheless, note the heavy role played by the branch nominals in this proof — for example at Steps 3, 6, 9, 10, 12, 14 and 16. In effect, the nominals and satisfaction operators allow us to build the desired model via its *diagram* (in the sense of first-order model theory). So it would actually be reasonable to describe the previous proof as a ‘modal Henkin construction’, where branch nominals play the role that would be played by constants in first-order logic. As we shall now see, the fact that we know how to build ‘modal Henkin models’, or ‘named models’, turns out to make life very simple when we examine what are called *locally definable* extensions of basic HOT logic.

4. Some extensions of HOT

We now examine three extensions of basic HOT logic. The most important point to note is that the completeness proof just given extends to all three systems in a simple and uniform way. Because the basic HOT logic contains all that is needed to build ‘modal Henkin models’, the extended systems we shall now discuss get a ‘free ride’ to completeness. This is very unusual in modal logic, where enriching a logic with (say) Until and Since operators may mean that an entirely new completeness proof strategy has to be used.

4.1. Adding Since and Until.

The operators **Since** and **Until** have the following Ockhamist semantics:

- $\mathcal{M}, b \models \mathbf{S}(\varphi, \psi)$ iff for some $c < b$, $\mathcal{M}, c \models \varphi$ and for every d , such that $c < d < b$, $\mathcal{M}, d \models \psi$;
- $\mathcal{M}, b \models \mathbf{U}(\varphi, \psi)$ iff for some $c > b$, $\mathcal{M}, c \models \varphi$ and for every d , such that $c > d > b$, $\mathcal{M}, d \models \psi$;

To axiomatize these operators in the HOT logic all we need is to the axioms:

$$\mathbf{c} \rightarrow (\mathbf{S}(\varphi, \psi) \leftrightarrow P(\varphi \wedge G(F\mathbf{c} \rightarrow \psi))),$$

$$\mathbf{c} \rightarrow (\mathbf{U}(\varphi, \psi) \leftrightarrow F(\varphi \wedge H(P\mathbf{c} \rightarrow \psi))).$$

Note that these axioms in a sense define the Since and Until operators at a named branch \mathbf{c} . (To use the terminology introduced shortly, they *locally define* Since and Until). It follows that the completeness proof remains unchanged, save for the additional clauses in the Truth lemma, corresponding to **S** and **U**. And these are *immediate* consequences of the inductive hypothesis and the axioms just

given. For as the canonical model is named, we can apply modus ponens and pull out the definitions of Since and Until, and these will enable the truth lemma to be proved.

Remark 4.1 *This is a particular case of a more general phenomenon, viz. locally definable operators (see [13]). A new operator $\mathbf{O}(\overline{p}, \overline{b})$ where $\overline{p}, \overline{b}$ are tuples of variables, resp nominals, is **locally definable** in the hybrid language if there is a formula $\varphi(\overline{p}, \overline{b}, \mathbf{c})$ such that*

$$\models \mathbf{c} \rightarrow (\mathbf{O}(\overline{p}, \overline{b}) \leftrightarrow \varphi(\overline{p}, \overline{b}, \mathbf{c})).$$

This formula, added as an axiom preserves the completeness of the hybrid logic.

Remark 4.2 *The full computation tree logic CTL* can be considered as a particular case of the extension of the HOT logic with Until considered over ω -trees (i.e. trees in which every path has the order type of ω). Indeed, the Nexttime operator is definable as usual by $X\varphi := \perp U\varphi$, and the path quantifier $\forall\varphi$ is simply $\Box\varphi$.*

4.2. Adding binders.

So let us now add the standard hybrid **binder** \downarrow . This has the following semantics:

$$\mathcal{M}, b \models \downarrow_{\mathbf{b}} \varphi \text{ iff } \mathcal{M}', b \models \varphi \text{ where } \mathcal{M}' \text{ is obtained from } \mathcal{M} \text{ by possibly modifying the valuation } V \text{ in } \mathcal{M} \text{ to } V' \text{ as follows: } V'(\mathbf{b}) = b; V'(\mathbf{c}) = V(\mathbf{c}) \text{ for every } \mathbf{c} \neq \mathbf{b}.$$

That is, $\downarrow_{\mathbf{b}}$ binds a nominal to the current branch — so to speak, it creates a new branch name on-the-fly.

The introduction of the \downarrow binder greatly increases the expressive power at our disposal. However axiomatizing its logic leads to no extra work, for \downarrow is locally definable by:

$$(\downarrow) \mathbf{c} \rightarrow (\downarrow_{\mathbf{b}}\varphi \leftrightarrow \varphi(\mathbf{c}/\mathbf{b})).$$

This formula axiomatizes completely \downarrow over our basic HOT axiomatic system.

Furthermore, note that in the presence of \downarrow every operator $\mathbf{O}(\overline{p}, \overline{b})$ locally definable by a formula $\varphi(\overline{p}, \overline{b}, \mathbf{c})$ becomes *explicitly definable* by

$$\mathbf{O}(\overline{p}, \overline{b}) = \downarrow_{\mathbf{c}}\varphi(\overline{p}, \overline{b}, \mathbf{c}).$$

Once again, we remark that the \downarrow binder is related to the freeze quantifiers used in half-order modal logic, which was introduced, developed, and applied to real-time logics by Alur and Henzinger (see [3], [15], [4]). The connections between hybrid logics equipped with the \downarrow binder and half-order modal logic deserve further exploration.

4.3. Adding branch quantifiers

If we are prepared to bind branch nominals, why not go the whole way and quantify across them? In fact, the idea of quantifying over nominals has been around since the late 1960s (see [16, 10]). Incidentally, [10] discusses a language in which nominals range over branches through time.

The universal quantifier over nominals in hybrid languages has the following semantic definition:

$$\mathcal{M}, b \models \forall \mathbf{b}\varphi \text{ iff } \mathcal{M}', b \models \varphi \text{ for every } \mathcal{M}' \text{ obtained from } \mathcal{M} \text{ by possibly re-defining the valuation } V \text{ in } \mathcal{M} \text{ on } \mathbf{b}.$$

To cope with this addition, we enrich the basic HOT axiomatization as follows. First we add the standard first-order quantifier axioms:

($\forall 1$) $\forall \mathbf{b}(\varphi \rightarrow \psi) \rightarrow (\varphi \rightarrow \forall \mathbf{b}\psi)$ for \mathbf{b} not occurring in φ .

($\forall 2$) $\forall \mathbf{b}\varphi \rightarrow \varphi(\mathbf{c}/\mathbf{b})$ for any nominal \mathbf{c} .

We also add the standard first-order rule of generalization: if φ is provable, so $\forall \mathbf{b}\varphi$.

Then, we add hybrid analogs of Barcan's formula:

(Bar) $\forall \mathbf{b}\nabla\varphi \rightarrow \nabla\forall \mathbf{b}\varphi$ for $\nabla \in \{\Box, G, H\}$

These axioms added to HOT+(\downarrow) axiomatize completely the *full hybrid Ockhamist temporal logic* FHOT.

Two remarks. First we note that FHOT is expressively equivalent to the first-order logic over trees extended with branch quantifiers, proved decidable in [14]. Second, FHOT is also expressively equivalent to the \downarrow system just discussed. For in the presence of the sometime modality, the downarrow binder is capable of defining the hybrid quantifiers as follows: $\exists \mathbf{b}\varphi = \downarrow_{\mathbf{c}} E \downarrow_{\mathbf{b}} E(\mathbf{c} \wedge \varphi)$, where \mathbf{c} does not occur in φ .

References

- [1] C. Areces, *Logic Engineering. The Case of Description and Hybrid Logics*, ILLC Dissertation series DS-2000-05, University of Amsterdam. Available at the hybrid logic homepage, www.hylo.net.
- [2] C. Areces, P. Blackburn, and M. Marx, The Computational Complexity of Hybrid Temporal Logics, *Logic Journal of IGPL*, 8(5), 2000, 653–679.
- [3] R. Alur and T. Henzinger, A Really Temporal Logic. *Journal of the ACM*, 41, 1994, 181-204; a preliminary version appeared in the *Proc. 30th FOCS*, 1989.
- [4] R. Alur and T. Henzinger, Logics and Models of Real Time: A Survey. In: *Real-Time: Theory in Practice*, REX Workshop, LNCS 600, pp. 74-106, 1991.

- [5] N. Belnap, Branching Space-time, *Synthese*, 92, 1992, 385-434.
- [6] P. Blackburn, Representation, Reasoning, and Relational Structures: a Hybrid logic Manifesto, *Logic Journal of IGPL*, 8(3), 2000, 339-365.
- [7] P. Blackburn and M. Tzakova, Hybrid Languages and Temporal Logic, *Logic Journal of IGPL*, 7(1), 1999, 27-54.
- [8] P. Blackburn, M. de Rijke, and Y. Venema, *Modal Logic*, Cambridge Tracts in Theoretical Computer Science, Cambridge University Press, 2001.
- [9] M. Brown and V. Goranko, An Extended Branching-Time Ockhamist Temporal Logic, *Journal of Logic, Language and Information*, 8(2), 1999, 143-166.
- [10] R. Bull, An Approach to Tense Logic, *Theoria*, 36(3), 1970, 282-300.
- [11] J. Burgess, Decidability for Branching Time, *Studia Logica*, 39, 2/3 (1980), 203-218.
- [12] E. Emerson, *Temporal and Modal Logic*, in: *Handbook of Theoretical Computer Science*, vol. B, J. van Leeuwen (ed.), Elsevier, 1990, pp. 995-1072.
- [13] V. Goranko, Hierarchies of Modal and Temporal Logics with Reference Pointers, *Journal of Logic, Language and Information*, 5, 1996, 1-24.
- [14] Y. Gurevich and S. Shelah, The Decision Problem for Branching-Time Logic, *Journal of Symbolic Logic*, 50(3), 1985, 668-681.
- [15] T. Henzinger, Half-Order Modal Logic: How to Prove Real-Time Properties, in: *Proceedings of the Ninth Annual ACM Symposium on Principles of Distributed Computing (PODC 1990)*, pp. 281-296.
- [16] A. Prior, *Past, Present, and Future*, Clarendon Press, Oxford, 1967.
- [17] C. Stirling, Modal and Temporal Logics, in: *Handbook of Logic in Computer Science*, vol. 2: *Computational Structures*, S. Abramski, D. Gabbay, T. Maibaum (eds.), Clarendon Press, Oxford, 1992, 478-563.
- [18] R. Thomason, Combinations of Tense and Modality, in: *Handbook of Philosophical Logic*, vol. II, D. Gabbay, F. Guenther (eds.), Reidel, Dordrecht, 1984, 135-165.
- [19] A. Zanardo, Branching-Time Logic with Quantification Over Branches: The Point of View of Modal Logic, *Journal of Symbolic Logic*, 61(1), 1996, 1-39.